

ENCLOSED CARGO 4 / 5 / 6-WIDE

- Integrated All-Aluminum Box Tube
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2" x 3" Subframe Tubing
- Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- 2 Interior LED Dome Lights w/ Switch
- Rear Barn Doors
- Polished Aluminum Fenders
- 24" Bright Stoneguard
- 3/8" Water Resistant Walls
- 32"x66" Side Door (6 wides only)
- 3/4" Water Resistant Decking (6 wides)
- 5/8" Water Resistant Decking (4 & 5 wides)
- Recessed LED Lights
- 2000# Center Jack
- (2) 5000# Safety Chains
- Roof Vent
- Limited Lifetime Warranty

STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MEC4x6-IF	MEC5x8-IF	MEC5x10-IF	MEC6x10-IF	MEC6x12SA-IF	MEC6x12TA-IF
Box WxLxH	50" x 6' x 60"	60" x 8' x 66"	60" x 10' x 66"	72" x 10' x 78"	72" x 12' x 78"	72" x 12' x 78"
Interior WxLxH	47" x 5'10" x 58"	57" x 7'10" x 64"	57" x 9'10" x 64"	69" x 9'10" x 76"	69" x 11'10" x 76"	69" x 11'10" x 76"
Overall WxLxH	72" x 10' x 72"	82" x 12'8" x 78"	82" x 14'8" x 78"	94" x 15'7" x 90"	94" x 17'7" x 90"	94" x 19'7" x 90"
Deck Height	12"	13"	13"	13"	13"	13"
Rear Door Opening WxH	42" x 54"	52" x 60"	52" x 60"	64" x 72"	64" x 72"	64" x 72"
Axle(s) - Qty/Rating	1-2200#	1-3500#	1-3500#	1-3500#	1-3500#	2-3500#
Wheels	13" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod
Tires	175/80R13	205/75R15	205/75R15	205/75R15	205/75R15	205/75R15
GVWR	2200#	2990#	2990#	2990#	2990#	7000#
Curb Weight	650#	875#	950#	1120#	1300#	TBD
Payload	1550#	2115#	2040#	1870#	1690#	TBD
V-Nose	24"	28"	28"	38 1/2"	38 1/2"	38 1/2"
Coupler Rating/Ball Size	3500#/2"	3500#/2"	3500#/2"	8000#/2"	8000#/2"	8000#/2"
Hitch Height	11"	12"	12"	12"	12"	12"
Power Connection	4-Way Flat	4-Way Flat	4-Way Flat	4-Way Flat	4-Way Flat	7-Way Round

ENCLOSED CARGO 7-WIDE

STANDARD FEATURES

- Intergrated All-Aluminum Box Tube
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2" x 3" Heavy Wall Subframe Tubing (2"x5" Tongue)
- Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Barn Doors
- 3/4" Water Resistant Decking
- Polished Aluminum Fenders
- 32"x66" Side Access Door
- 24" Bright Stoneguard
- 3/8" Water Resistant Walls
- 3 Interior LED Dome Lights w/ Switch
- Roof Vent
- Recessed LED Lights
- Tri-Frame Tongue
- A-Frame Coupler w/ 2 5/16" Ball
- 2000# Center Jack
- (2) 5000# Safety Chains
- Limited Lifetime Warranty

STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MEC7x12-IF	MEC7x14-IF	MEC7x16-IF	MEC7x18-IF	MEC7x20-IF
Box WxLxH	84"x12"x78"	84"x14"x78"	84"x16"x78"	84"x18"x78"	84"x20"x78"
Interior WxLxH	81"x11'10"x76"	81"x13'10"x76"	81"x15'10"x76"	81"x17'10"x76"	81"x19'10"x76"
Overall WxLxH	102"x17'10"x90"	102"x19'10"x90"	102"x21'10"x90"	102"x23'10"x90"	102"x23'10"x90"
Deck Height	13"	13"	13"	13"	13"
Hitch Height	12"	12"	12"	12"	12"
Rear Door Opening	76"x72"	76"x72"	76"x72"	76"x72"	76"x72"
Axle(s) - Qty/Rating)	2-3500#	2-3500#	2-3500#	2-3500#	2-3500#
Wheels	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod
Tires	205/75R15	205/75R15	205/75R15	205/75R15	205/75R15
GVWR	7000#	7000#	7000#	7000#	7000#
Curb Weight	1450#	1750#	1900#	2075#	2275#
Payload	5550#	5250#	5100#	4925#	4725#
Wheel Jack	Standard	Standard	Standard	Standard	Standard
Power Connection	7-Way Round	7-Way Round	7-Way Round	7-Way Round	7-Way Round

ENCLOSED CARGO 7.5-WIDE

STANDARD FEATURES

- Intergrated All-Aluminum Box Tube
- 24" Bright Stoneguard
- 16" O/C Wall & Roof Studs
- 3/8" Water Resistant Walls
- 24" O/C Floor Crossmembers
- 3 Interior LED Dome Lights w/ Switch
- 2" x 3" Heavy Wall Subframe Tubing (2"x5" Tongue)
- Roof Vent
- Torsion Ride Suspension
- Recessed LED Lights
- Smooth .030" Bonded Side Panels
- Tri-Frame Tongue
- One-Piece Aluminum Roof
- A-Frame Coupler w/ 2 5/16" Ball
- Rear Barn Doors
- 2000# Center Jack
- 3/4" Water Resistant Decking
- (2) 5000# Safety Chains
- Polished Aluminum Fenders
- Limited Lifetime Warranty
- 32"x66" Side Access Door

STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MEC7.5x12-IF	MEC7.5x14-IF	MEC7.5x16-IF	MEC7.5x18-IF	MEC7.5x20-IF
Box WxLxH	90"x12"x78"	90"x14"x78"	90"x16"x78"	90"x18"x78"	90"x20"x78"
Interior WxLxH	87"x11"10"x76"	87"x13"10"x76"	87"x15"10"x76"	87"x17"10"x76"	87"x19"10"x76"
Overall WxLxH	102"x17"10"x90"	102"x19"10"x90"	102"x21"10"x90"	102"x23"10"x90"	102"x23"10"x90"
Deck Height	13"	13"	13"	13"	13"
Hitch Height	12"	12"	12"	12"	12"
Rear Door Opening	80"x72"	80"x72"	80"x72"	80"x72"	80"x72"
Axle(s) - Qty/Rating)	2-3500#	2-3500#	2-3500#	2-3500#	2-3500#
Wheels	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod
Tires	205/75R15	205/75R15	205/75R15	205/75R15	205/75R15
GVWR	7000#	7000#	7000#	7000#	7000#
Curb Weight	1450#	1750#	1900#	2075#	2275#
Payload	5550#	5250#	5100#	4925#	4725#
Wheel Jack	Standard	Standard	Standard	Standard	Standard
Power Connection	7-Way Round	7-Way Round	7-Way Round	7-Way Round	7-Way Round

ENCLOSED CARGO 8.5-WIDE

STANDARD FEATURES

- Integrated All-Aluminum Box Tube
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2" x 5" Subframe Tubing
- Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Barn Doors
- 3/4" Water Resistant Decking
- Polished Aluminum Fenders
- 32"x66" Side Door
- 24" Bright Stoneguard
- 3/8" Water Resistant Walls
- 3 Interior LED Dome Lights w/ Switch
- Roof Vent
- Recessed LED Lights
- Tri-Frame Tongue
- A-Frame Coupler w/ 2 5/16" Ball
- 2000# Center Jack
- (2) 5000# Safety Chains
- Limited Lifetime Warranty

STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MEC8.5x12-IF	MEC8.5x14-IF	MEC8.5x16-IF	MEC8.5x18-IF	MEC8.5x20-IF
Box WxLxH	99"x12"x78"	99"x14"x78"	99"x16"x78"	99"x18"x78"	99"x20"x78"
Interior WxLxH	96"x11'10"x76"	96"x13'10"x76"	96"x15'10"x76"	96"x17'10"x76"	96"x19'10"x76"
Overall WxLxH	102"x18'8"x92"	102"x20'8"x92"	102"x22'8"x92"	102"x24'8"x92"	102"x26'8"x92"
Deck Height	15"	15"	15"	15"	15"
Hitch Height	14"	14"	14"	14"	14"
Rear Door Opening	89"x72"	89"x72"	89"x72"	89"x72"	89"x72"
Axle(s) - Qty/Rating	2-3500#	2-3500#	2-3500#	2-3500#	2-3500#
Wheels	15" Silver Mods	15" Silver Mods	15" Silver Mods	15" Silver Mods	15" Silver Mods
Tires	205/75R15	205/75R15	205/75R15	205/75R15	205/75R15
GVWR	7000#	7000#	7000#	7000#	7000#
Curb Weight	1850#	1950#	2050#	2275#	2475#
Payload	5150#	5050#	4950#	4725#	4525#
Wheel Jack	Standard	Standard	Standard	Standard	Standard
Power Connection	7-Way Round	7-Way Round	7-Way Round	7-Way Round	7-Way Round

ENCLOSED MOTORCYCLE

STANDARD FEATURES

- Intergrated All-Aluminum Box Tube
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2" x 3" Heavy Wall Subframe Tubing
- Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Ramp Door w/ Spring Assist
- 3/4" Water Resistant Decking
- Polished Aluminum Fenders
- 24" Bright Stoneguard
- 32"x58" Side Access Door
- White Luan Interior Walls
- 3 Interior LED Dome Lights w/ Switch
- Roof Vent
- Recessed LED Lights
- 7-Way Round Power Connection
- Tri-Frame Tongue
- 8000# A-Frame Coupler w/ 2" Ball
- 2000# Center Jack
- (2) 7800# Safety Chains
- Limited Lifetime Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MEM7x12LP-IF	MEM7x14LP-IF
Box WxLxH	84"x12'x72"	84"x14'x72"
Interior WxLxH	81"x11'10"x70"	81"x11'10"x70"
Overall WxLxH	102"x18'4"x85"	102"x20'2"x85"
Deck Height	13"	13"
Hitch Height	12"	12"
Rear Door Opening	74"x66"	74"x66"
Axle(s) - Qty/Rating	2-3500#	2-3500#
Wheels	15" T07 Aluminum	15" T07 Aluminum
Tires	205/75R15	205/75R15
GVWR	6000#	6000#
Curb Weight	1525#	1700#
Payload	4475#	4300#