

ENCLOSED SNOW [INLINE] 7-Wide

STANDARD FEATURES

- All-Aluminum Construction
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2"x5" Subframe Tubing
- Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Ramp Door w/ Spring Assist
- Front Ramp Door w/ Spring Assist
- 3/4" Water Resistant Decking
- Polished Aluminum Fenders
- Full Length Slide Track w/ D-Rings
- 24" Bright Stoneguard
- White Luan Walls w/ 12" WR Kickplate
- 3 Interior Dome Lights
- Roof Vent
- Recessed LED Lights
- Tri-Frame Tongue
- 8000# A-Frame Coupler w/ 2" Ball
- 1500# Wheel Jack
- (2) 7800# Safety Chains
- 32"x66" Side Access Door
- Limited Lifetime Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MES7x12	MES7x14	MES7x16	MES7x18	MES7x22
Box WxLxH	7'x12'x78"	7'x14'x78"	7'x16'x78"	7'x18'x78"	7'x22'x78"
Interior WxLxH	81"x11'10x76"	81"x13'10x76"	81"x15'10x76"	81"x17'10x76"	81"x21'10x76"
Overall WxLxH	101"x18'9"x8'7"	101"x20'9"x8'7"	101"x22'9"x8'7"	101"x24'9"x8'7"	101"x28'9"x8'7"
Deck Height	21"	21"	21"	21"	21"
Hitch Height	16"	16"	16"	16"	16"
Rear Door Opening WxH	74" x 72 1/4"	74" x 72 1/4"	74" x 72 1/4"	74" x 72 1/4"	74" x 72 1/4"
Front Door Opening WxH	55" x 72"	55" x 72"	55" x 72"	55" x 72"	55" x 72"
Axle(s) - Qty/Rating	1-3500#	2-3500# Braked	2-3500# Braked	2-3500# Braked	2-3500# Braked
Wheels	15" Silver Mods	15" Silver Mods	15" Silver Mods	15" Silver Mods	15" Silver Mods
Tires	205/75R15	205/75R15	205/75R15	205/75R15	205/75R15
GVWR	2990#	6000#	6000#	6000#	6000#
Curb Weight	1450#	1700#	1850#	2000#	2175#
Payload	1540#	4300#	4150#	4000#	3825#
Power Connection	4-Way Flat	7-Way Round	7-Way Round	7-Way Round	7-Way Round

ENCLOSED SNOW [INLINE] 7.5-Wide

STANDARD FEATURES

- All-Aluminum Construction
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2"x5" Subframe Tubing
- Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Ramp Door w/ Spring Assist
- Front Ramp Door w/ Spring Assist
- 3/4" Water Resistant Decking
- Polished Aluminum Fenders
- 24" Bright Stoneguard
- Full Length Slide Track w/ D-Rings
- White Luan Walls w/ 12" WR Kickplate
- 3 Interior Dome Lights
- Roof Vent
- Recessed LED Lights
- Tri-Frame Tongue
- 8000# A-Frame Coupler w/ 2" Ball
- 1500# Wheel Jack
- (2) 7800# Safety Chains
- 32"x66" Side Access Door
- Limited Lifetime Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MES7.5x12	MES7.5x14	MES7.5x16	MES7.5x18	MES7.5x22
Box WxLxH	7'6"x12'x78"	7'6"x14'x78"	7'6"x16'x78"	7'6"x18'x78"	7'6"x22'x78"
Interior WxLxH	87"x11'10"x76"	87"x13'10"x76"	87"x15'10"x76"	87"x17'10"x76"	87"x21'10"x76"
Overall WxLxH	101"x18'8"x8'7"	101"x20'8"x8'7"	101"x22'8"x8'7"	101"x24'8"x8'7"	101"x28'8"x8'7"
Deck Height	21"	21"	21"	21"	21"
Hitch Height	16"	18"	18"	18"	18"
Rear Door Opening WxH	74" x 72 1/4"	74" x 72 1/4"	74" x 72 1/4"	74" x 72 1/4"	74" x 72 1/4"
Front Door Opening WxH	55" x 72"	55" x 72"	55" x 72"	55" x 72"	55" x 72"
Axle(s) - Qty/Rating	1-3500# Idler	2-3500# Braked	2-3500# Braked	2-3500# Braked	2-3500# Braked
Wheels	15" Silver Mods	15" Silver Mods	15" Silver Mods	15" Silver Mods	15" Silver Mods
Tires	205/75R15	205/75R15	205/75R15	205/75R15	205/75R15
GVWR	2990#	6000#	6000#	6000#	6000#
Curb Weight	1525#	1775#	1855#	1935#	2100#
Payload	1375#	4225#	4145#	4065#	3900#
Power Connection	4-Way Flat	7-Way Round	7-Way Round	7-Way Round	7-Way Round

ENCLOSED SNOW [DECKOVER] DURALITE

STANDARD FEATURES

- All-Aluminum Construction
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2"x3" Subframe Tubing (2"x5" 18' +)
- Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Ramp Door w/ Spring Assist
- Front Ramp Door w/ Spring Assist
- 5/8" Water Resistant Decking
- 12" Water Resistant Kickplate
- 52" V-Nose
- Full Length Slide Track w/ D-Rings
- 12" Bright Stoneguard
- Recessed LED Lights
- Tri-Frame Tongue
- 6000# Straight Coupler w/ 2" Ball (12' & 14')
- 8000# A-Frame Coupler w/ 2" Ball (18' & 22')
- 1500# Wheel Jack
- (2) 7800# Safety Chains
- 32"x58" Side Access Door
- 4-Year Limited Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MES101x12DL	MES101x14DL	MES101x18DL	MES101x22DL
Box WxLxH	101"x12"x72"	101"x14"x72"	101"x18"x72"	101"x22"x72"
Interior WxLxH	98"x11'10"x70"	98"x13'10"x70"	98"x17'10"x70"	98"x21'10"x70"
Overall WxLxH	101"x17'5"x89"	101"x19'5"x89"	101"x23'5"x89"	101"x27'5"x89"
Deck Height	27"	27"	27"	27"
Hitch Height	19"	19"	23"	23"
Rear Door Opening	93"x68"	93"x68"	93"x68"	93"x68"
Front Door Opening	Optional	Optional	Optional	Optional
Axle(s) - Qty/Rating)	1-3500# Idler	2-2200# Braked	2-3500# Braked	2-3500# Braked
Wheels	12" E Rated	12" E Rated	13" Silver Mod	13" Silver Mod
Tires	ST145R12E	ST145R12E	ST175/80R13	ST175/80R13
GVWR	2990#	4400#	6000#	6000#
Curb Weight	1295#	1600#	TBD	TBD
Payload	1605#	2800#	TBD	TBD
Power Connection	4-Way Flat	7-Way Round	7-Way Round	7-Way Round

ENCLOSED SNOW [DECKOVER] 6.5-Height

STANDARD FEATURES

- All-Aluminum Construction
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2"x5" Subframe Tubing
- Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Ramp Door w/ Spring Assist
- Front Ramp Door w/ Spring Assist
- 3/4" Water Resistant Decking
- White Luan Walls w/ 12" WR Kickplate
- Full Length Slide Track w/ D-Rings
- 24" Bright Stoneguard
- 3 Interior Dome Lights
- Roof Vent
- Recessed LED Lights
- Tri-Frame Tongue
- 8000# A-Frame Coupler w/ 2" Ball
- 1500# Wheel Jack
- (2) 7800# Safety Chains
- 32"x66" Side Access Door
- Limited Lifetime Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MES101x12 (6.5)	MES101x14 (6.5)	MES101x20 (6.5)	MES101x22 (6.5)
Box WxLxH	101"x12'x78"	101"x14'x78"	101"x20'x78"	101"x22'x78"
Interior WxLxH	98"x11'10"x76"	98"x13'10"x76"	98"x19'10"x76"	98"x21'10"x76"
Overall WxLxH	101"x18'5"x8'8"	101"x20'5"x8'8"	101"x26'5"x8'8"	101"x28'5"x8'8"
Deck Height	27"	27"	27"	27"
Hitch Height	23"	23"	23"	23"
Rear Door Opening WxH	91" x 72"	91" x 72"	91" x 72"	91" x 72"
Front Door Opening WxH	58" x 72"	58" x 72"	58" x 72"	58" x 72"
Axle(s) - Qty/Rating	1-3500#	2-2200#	2-3500#	2-3500#
Wheels	12" E Rated	12" E Rated	13" Silver Mod	13" Silver Mod
Tires	ST145R12E	ST145R12E	175/80R13	175/80R13
GVWR	2990#	4400#	6000#	6000#
Curb Weight	1360#	1665#	2010#	2240#
Payload	1540#	2735#	3990#	3760#
Power Connection	4-Way Flat	7-Way Round	7-Way Round	7-Way Round

ENCLOSED SNOW [ALL-SPORT PEAK VALUE]

STANDARD FEATURES

- All-Aluminum Construction, 2" x 5" Main Frame
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- Dexter Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Ramp Door w/ Spring Assist w/FTH Flap
- Front Ramp Door w/ Spring Assist
- 3/4" Water Resistant Decking
- 4x Recessed D-Rings
- Polished Aluminum Fender Flares
- 48" Beavertail Construction
- White Luan Interior Walls & Ceiling
- Recessed LED Exterior Lights
- 3 Interior Dome Lights w/ Switch
- Drive-Over Fender Kit
- Roof Vent
- 12500# A-Frame Coupler w/ 2 5/16" Ball
- 32"x72" Side Access Door
- Tri-Frame Tongue
- 24" Bright Stoneguard
- HD Center Jack
- (2) 7800# Safety Chains
- Limited Lifetime Warranty



STANDARD SPECIFICATIONS

TRAILER MODEL	MCH8.5X16AS-PV	MCH8.5X18AS-PV	MCH8.5X22AS-PV	MCH8.5X24AS-PV
Box WxLxH	99"x16'x78"	99"x18'x78"	99"x22'x78"	99"x24'x78"
Interior WxLxH	96"x15'10"x6'4"	96"x17'10"x6'4"	96"x21'10"x6'4"	96"x23'10"x6'4"
Overall WxLxH	102"x23'9"x8'10"	102"x25'9"x8'10"	102"x29'9"x8'10"	102"x31'9"x8'10"
Deck Height	18"	18"	18"	18"
Rear Door Opening	89"x81"	89"x81"	89"x81"	89"x81"
Axle(s) - Qty/Rating)	2-3500# Braked	2-3500# Braked	2-3500# Braked	2-3500# Braked
Wheels	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod
Tires	205/75R15	205/75R15	205/75R15	205/75R15
GVWR	7000#	7000#	7000#	7000#
Curb Weight	TBD	TBD	TBD	TBD
Payload	TBD	TBD	TBD	TBD
Hitch Height	15"	15"	15"	15"

ALL-SPORT CAR HAULERS

STANDARD FEATURES

- All-Aluminum Construction
- 16" O/C Wall & Roof Studs
- 16" O/C Floor Crossmembers
- Torsion Ride Suspension
- Smooth .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Ramp Door w/ Spring Assist
- Front Ramp Door w/ Spring Assist
- w/ New FTH Flap System
- 3/4" Water Resistant Decking
- Polished Aluminum Fender Flares
- 48" Beavertail Construction
- White Luan Interior Walls & Ceiling
- Recessed LED Lights
- 3 Interior Dome Lights
- Drive-Over Fender Kit
- Roof Vent
- 12500# A-Frame Coupler w/ 2 5/16" Ball
- 32"x72" Side Access Door w/ Step Well
- Tri-Frame Tongue
- Recessed HD D-Rings
- Roof Vent
- 24" Bright Stoneguard
- HD Center Jack
- 5000# Wheel Jack
- (2) 7800# Safety Chains
- Limited Lifetime Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MCH8.5x16AS	MCH8.5x18AS	MCH8.5x20AS	MCH8.5x22AS	MCH8.5x24AS	MCH8.5x28AS	MCH8.5x32AS
Box WxLxH	99"x78"x16'	99"x78"x18'	99"x78"x20'	99"x78"x22'	99"x78"x24'	99"x78"x28'	99"x78"x32'
Interior WxLxH	96"x76"x15'10"	96"x76"x17'10"	96"x76"x19'10"	96"x76"x21'10"	96"x76"x23'10"	96"x76"x27'10"	96"x76"x31'10"
Overall WxLxH	102"x23'9"x8'8"	102"x25'9"x8'8"	102"x27'9"x8'8"	102"x29'9"x8'8"	102"x31'9"x8'10"	102"x35'9"x8'10"	102"x39'9"x8'10"
Subframe Tubing	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 8"	2" x 8"	2" x 8"
Deck Height	18"	18"	18"	18"	20"	20"	20"
Hitch Height	15"	15"	15"	15"	17"	17"	17"
Rear Door Opening WxH	89" x 75"	89" x 75"	89" x 75"	89" x 75"	89" x 75"	89" x 75"	89" x 75"
Front Door Opening	55" x 72"	55" x 72"	55" x 72"	55" x 72"	55" x 72"	55" x 72"	55" x 72"
Axle(s) - Qty/Rating	2-5200# Braked	2-5200# Braked	2-5200# Braked	2-5200# Braked	2-5200# Braked	2-5200# Braked	2-5200# Braked
Wheels	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod	15" Silver Mod
Tires	225/75R15	225/75R15	225/75R15	225/75R15	225/75R15	225/75R15	225/75R15
GVWR	9900#	9900#	9900#	9900#	9900#	9900#	9900#
Curb Weight	2415#	2850#	2900#	2950#	3050#	3250#	TBD
Payload	7485#	7050#	7000#	6950#	6850#	6650#	TBD

CROSSOVER SNOW 60" WIDE & 101" WIDES

STANDARD FEATURES

- All-Aluminum Construction
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2"x5" Subframe Tubing
- Torsion Ride Suspension
- Screwless .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Ramp Door w/ Spring Assist
- 19"x58" Front Access Door
- 5/8" Water Resistant Decking
- Full Length Slide Track w/ Ski Tie Down Bars (12' & 14' Models)
- Full Length Slide Track w/ Sliding D-Rings (16'+ Models)
- 12" Plywood Kickplate
- Interior Dome Light
- Louver Vents
- Recessed LED Lights
- Wishbone Tongue w/ Straight Coupler
- Round Radius Diamond Plate Nose
- 1200# Wheel Jack
- (2) 5000# Safety Chains
- Limited 4-Year Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MFS60x12CROSSOVER	MFS101x12CROSSOVER	MFS101x14CROSSOVER	MFS101x16CROSSOVER	MFS101x20CROSSOVER
Box WxLxH	60"x12"x66"	101"x12"x66"	101"x14"x66"	101"x16"x66"	101"x20"x66"
Interior WxLxH	57"x11'10"x64"	98"x11'10"x64"	98"x13'10"x64"	98"x15'10"x64"	98"x19'10"x64"
Overall WxLxH	80"x16'2"x85"	102"x7'8"x16'2"	102"x7'8"x18'2"	102"x7'8"x20'2"	102"x7'8"x24'2"
Deck Height	20"	25"	26"	26"	26"
Hitch Height	16"	23"	24"	24"	24"
Rear Door Opening	55" x 62"	93" x 62"	93" x 62"	93" x 62"	93" x 62"
Coupler Rating / Ball Size	3500#/2" Ball	3500#/2" Ball	6000#/2" Ball	6000#/2" Ball	6000#/2" Ball
Axle(s) - Qty/Rating	1-2200# Idler	1-3500#	2-2200# Braked	2-2200# Braked	2-2200# Braked
Wheels	13" Silver Mod	12" E-Rated	12" E-Rated	12" E-Rated	12" E-Rated
Tires	175/75R13	ST145/R12E	ST145/R12E	ST145/R12E	ST145/R12E
GVWR	2200#	2990#	4400#	4400#	4400#
Curb Weight	600#	1058#	TBD	TBD	1740#
Payload	1600#	1932#	TBD	TBD	2660#
Power Connection	4-Way Flat	4-Way Flat	7-Way Round	7-Way Round	7-Way Round

CROSSOVER SNOW 7 & 7.5 WIDES

STANDARD FEATURES

- All-Aluminum Construction
- 16" O/C Wall & Roof Studs
- 24" O/C Floor Crossmembers
- 2"x4" Subframe Tubing (2"x5" 18'+)
- Torsion Ride Suspension
- Screwless .030" Bonded Side Panels
- One-Piece Aluminum Roof
- Rear Ramp Door w/ Spring Assist
- 19"x58" Front Access Door
- 5/8" Water Resistant Decking
- 12" Plywood Kickplate
- Full Length Slide Track w/ Sliding D-Rings
- Screwed .030" Bonded Side Panels (7x16 SA is Screwless)
- Interior Dome Light
- Louver Vents
- Recessed LED Lights
- Wishbone Tongue w/ Straight Coupler
- Round Radius Diamond Plate Nose
- 1200# Wheel Jack
- (2) 5000# Safety Chains
- Limited 4-Year Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MFS7x16CROSSOVER	MFS7.5x16CROSSOVER	MFS7.5x22CROSSOVER
Box WxLxH	84"x16'x66"	90"x16'x66"	90"x22'x66"
Interior WxLxH	81"x15'10"x64"	87"x15'10"x64"	87"x21'10"x64"
Overall WxLxH	102"x20'2"x84"	102"x20'2"x84"	102"x26'2"x84"
Deck Height	19"	19"	19"
Hitch Height	15"	15"	15"
Rear Door Opening	76" x 62"	82" x 62"	82" x 62"
Coupler Rating / Ball Size	6000#/2" Ball	6000#/2" Ball	6000#/2" Ball
Axle(s) - Qty/Rating	1-3500# Idler	2-2200# Braked	2-3500# Braked
Wheels	15" Silver Mods.	15" Silver Mods.	15" Silver Mods.
Tires	ST205/75R15	ST205/75R15	ST205/75R15
GVWR	2990#	4400#	6000#
Curb Weight	1455#	1390#	TBD
Payload	1535#	3010#	TBD
Power Connection	4-Way Flat	7-Way Round	7-Way Round