

OPEN MOTORCYCLE TRAILERS

5'x8' & 6.5'x10'



5'x8' & 6.5'x10'

STANDARD FEATURES

- > All Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > 3500# Straight-Pull Style Coupler w/2" Ball
- > (2) 5000# Safety Chains
- > Dexter Torsion Ride Axles
- > Easy Removable Aluminum Fenders
- > Extruded Aluminum Decking
- > HD Aluminum Pull-Out Ramp (36"x60"
- Ramp; For 5x8 Trailer)
- > HD Aluminum Pull-Out Ramp (46"x60"
- Ramp; For 6.5x10 Trailer)
- > Removable 18" Aluminum Stone Guard
- > (2) Surface-Mounted Aluminum Wheel
- Chocks (Gusseted, Fits Up to 7" Wide Tire)
- > Recessed LED Marker Lights
- > Adjustable Perimeter Track for Easy Install Options
- > 5-Year Limited Warranty

STANDARD SPECIFICATIONS

TRAILER MODEL	OPEN MOTORCYCLE 5X8	OPEN MOTORCYCLE 6.5X10
Model Number	MOMC5X8-2.0	MOMC6.5X10-2.0
Deck (WxL)	56"x96"	76"x120"
Overall (WxL)	82"x170"	102"x204"
Deck Height	16"	18"
Hitch Height	13"	14"
Axle(s) - Qty/Rating	1-2200# Idler	1-3500# Idler
Wheels	13" Aluminum	14" Aluminum
Tires	175/80R13	205/75R14
GVWR	2200#	2990#
Curb Weight	400#	550#
Payload	1800#	2440#
Easy-Adjust D-Rings	4	8
Wheel Jack	1200#	1500#
Power Connection	4-Way Flat	4-Way Flat

OPTIONS & ACCESSORIES

TIRE/WHEEL ASSEMBLIES & ACCESSORIES	ACCESSORIES
Spare 13" Aluminum Wheel w/ 175/80R13 Tire	Stabilizer Jacks (Installed; Pair)
Spare 14" Aluminum Wheel w/ 205/75R14 Tire	EASY INSTALL/ADJUST OPTIONS
Upgrade to 14" Aluminum (Radial Ply; From 13" Aluminum; Open Trailers)	Easy Install/Adjust Spare Tire Mount (AR or FA 2.0)
Upgrade to 15" Aluminum (Radial Ply; From 14" Aluminum Wheels; Open Trailers)	Easy Install/Adjust Stake Pocket Kit (AR or FA 2.0): (4) Stake Pockets w/ Hardware
RAMP OPTIONS	Easy Install/Adjust D-Ring Kit (AR or FA 2.0): Includes (4) 2,000lb D-Rings and Hardware
Upgrade to Full Width Ramp (Open Motorcycle Trailer)	Easy Install/Adjust D-Ring (AR or FA 2.0)
Upgrade to Rear Ramp (Open MC Models; Replaces Stowaway Ramp)	Easy Install/Adjust Drop Down Stabilizer Jacks (Pair)
TIE DOWN OPTIONS	
Light Duty Surface-Mounted D-Ring (Installed)	

RAMP CAPACITY BY MODEL

Ramp Type	Applicable Models	Capacity
Utility Trailer Rear Ramp (Fold-Down)	SSR (All Sizes); AR 2.0 (All Sizes); WR 2.0 (All Sizes); FA 2.0 (All Sizes); Landscape (LS) 2.0 (All Sizes)	750#
Utility Trailer Rear Ramp (Fold-Down, Bi-Fold)	SSR (Optional, All Sizes); AR 2.0 (Optional, All Sizes); WR 2.0 (Optional, All Sizes); FA 2.0 (Optional, All Sizes); Landscape (LS) 2.0 (Optional, All Sizes)	750#
Deckover Equipment Trailer Ramps (Stow)	(All Sizes)	4000# (PAIR)
Deckover Equipment Trailer Ramps 14K (Fold-Down)	(All Sizes)	5000# (PAIR)
Patriot Ramps (Fold-Down)	(All Sizes)	4000# (PAIR)
Patriot Ramps 14K (Fold-Down)	(All Sizes)	5000# (PAIR)
Dump Trailer Ramps (Side-Stow, Optional)	(All Sizes)	4000# (PAIR)
ATV Ramps (83" Wide, Side-Stow)	(All Sizes)	1200# (PAIR)
ATV Ramps (88" Wide, Side-Stow)	(All Sizes)	750# (PAIR)
Open Motorcycle Ramp (Rear-Stow)	(All Sizes)	1200#
Slingshot Rear Ramp (Fold-Down, Bi-Fold)	MU-SLINGSHOT	1500#
Open Car Hauler 2.0 Ramps (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler 2.0 Ramps 10K (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler Standard Ramps (Stow)	(All Sizes)	4000# (PAIR)
Open Snow Ramp (Rear-Stow)	MFS	750#
Sport Deck (Rear-Stow, Telescoping Ramps)	MSD	1000#
Enclosed Cargo Ramp (4', 5', 6' Wide)	(All Sizes)	1500#
Enclosed Cargo Ramp (7' 7.5' Wide)	(All Sizes)	1500#
Enclosed Cargo Ramp (8.5' Wide, Premium)	(All Sizes)	1500#
Enclosed Motorcycle Ramp (7' Wide)	(All Sizes)	1500#
Enclosed Car Hauler Ramp (8.5' Wide)	(All Sizes)	4000#
Enclosed Gooseneck Ramp (8.5' Wide, Rear)	(All Sizes)	4000#
Enclosed Gooseneck Ramp (8.5' Wide, Side, Optional)	(All Sizes)	1200#
Enclosed Snowmobile Ramp (7', 7.5', 101" Wide, Rear)	(All Sizes)	1500#
Enclosed Snowmobile Ramp (7', 7.5', 101" Wide, Front)	(All Sizes)	1200#
Enclosed Snowmobile Ramp (Crossover, Rear)	(All Sizes)	1500#

TONGUE EXTENSION BY MODEL

TRAILER TYPE	ALLOWABLE EXTENSION	ADDITIONAL REQUIREMENTS	ITEM NUMBER	DESCRIPTION
Enclosed Cargo (4, 5-Wide)	N/A	FRAME UPGRADE REQUIRED, CONSULT ENGINEERING	N/A	N/A
Enclosed Cargo (6, 7, 7.5-Wide)	12"	ECONOMY MODELS REQUIRE CENTER BEAM UPGRADE	TONGUE12EXT	12" Extended Tongue (For 3k Tandem Axle Enclosed with 2"x5" Frame) Includes Center Beam Upgrade ** CANNOT DO WITH ALL SPORTS OR SNOW TRAILERS **
Enclosed Cargo (8.5-Wide, Premium)	12" (16" w/ UPGRADE)	MIN 6" FRAME FOR 16" TONGUE EXTENSION, UPGRADE MAY BE REQUIRED	TONGUE12EXT	12" Extended Tongue (For 3k Tandem Axle Enclosed with 2"x5" Frame) Includes Center Beam Upgrade ** CANNOT DO WITH ALL SPORTS OR SNOW TRAILERS **
Enclosed Motorcycle (7-Wide)	12"		TONGUE12EXT	12" Extended Tongue (For 3k Tandem Axle Enclosed with 2"x5" Frame) Includes Center Beam Upgrade ** CANNOT DO WITH ALL SPORTS OR SNOW TRAILERS **
Enclosed Car Hauler (8.5-Wide, Premium)	16"		TONGUE16EXTCH	16" Extended Tongue (For 5k Tandem Axle Enclosed; Trailer Must have 2"x6" Frame or Larger) ** CANNOT DO WITH ALL SPORTS OR SNOW TRAILERS **
Enclosed Car Hauler - All Sports (8.5-Wide)	N/A	EXTENDED TONGUE INCOMPATIBLE WITH FRONT RAMP	N/A	N/A
Enclosed Snowmobile (7, 7.5-Wide)	N/A	EXTENDED TONGUE INCOMPATIBLE WITH FRONT RAMP	N/A	N/A
Enclosed Snowmobile (101-Wide)	10"	REQUIRES 3x5 TONGUE UPGRADE w/ STRAIGHT-PULL COUPLER	TBD	TBD

**Please note that all 5k tandem trailers w/ extended tongues require a minimum of 6" base frame, regardless of brand/model