

RAFT SERIES

STANDARD FEATURES

- All-Aluminum Construction
- 24" O/C Crossmembers
- 2"x3" Subframe Tubing
- 5/4" Pressure Treated Decking
- Torsion Ride Axles
- Manual Winch w/ 24" Post
- Rear Roller w/ Bearings
- Recessed LED Marker Lights
- (5) Tie Down Points per Side
- (2) Front Tie Down Points
- 4-Way Flat Power Connection
- 6000# Straight Coupler w/ 2" Ball
- (2) 5000# Safety Chains
- Limited 1-Year Warranty



STANDARD SPECIFICATIONS & PRICING

TRAILER MODEL	MRFT84x10	MRFT84x12
Deck WxL	84"x10'	84"x12'
Overall WxL	84"x14'	84"x16'
Deck Height	26"	26"
Hitch Height	21"	21"
Axle(s) - Qty/Rating	1-2200#	1-2200#
Wheels	13" Silver Mods	13" Silver Mods
Tires	175/80R13	175/80R13
GVWR	2200#	2200#
Curb Weight	540#	590#
Payload	1660#	1610#

BASE PRICE

POPULAR OPTIONS

CONSTRUCTION OPTIONS	PRICE	UOM
Upgrade to 36" Winch Post		EA
Tilt Bed Option		EA
Welded Side Tie Down Rings		EA
WHEELS		
Spare 13" Silver Mod (175/80R15)		EA
Upgrade to 13" Aluminum Rims from 13" Silver Mod		EA
Spare 13" Aluminum Rim (175R13")		EA
Tongue Mounted Spare Mount (Bolt-On)		EA
ACCESSORIES		
1200# Wheel Jack		EA
Additional Surface-Mount D-Rings		EA